

ROOF SEAL MASTIC

Repair Mastic SBS



PRODUCT DATA SHEET



Product description

A very elastic, bitumen, waterproof paste for sealing seams, cracks and tears. It can also be used to fill roof edges, wall trim flashings, rainwater drains, skylights, capping stones, chimneys, roof windows and other upstands. Adheres well to different substrates, even if damp.

Application

For use on bitumen substrates, wood, metal, various types of plastics, stone, concrete and insulation panels.

Advantages

- › All substrates
- › Very elastic
- › Waterproof
- › Easy to apply and easy to use
- › Resistant to all weather conditions

How much product do I need?

That depends on the area or details to be treated.

Handy tips?

- Store in a dry and cool place.
- Clean your tools with white spirit or turpentine.
- When treating larger areas or cracks, use **ROOF REPAIR REGULAR**, which comes in 1 kg or 2.5 kg.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Bitumen with fibres	Black	310 ml	Depends on the area or details to be treated	/	1	No

ROOF SEAL MASTIC

Repair Mastic SBS



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- Remove all dust and grease from the substrate.
- Combat any green mould, lichens and algae with **GARDEN CLEAN GREEN REMOVER**.

How do I use the product?

- Cut the tube open near the thread, install the nozzle and cut it to achieve the desired width.
- Apply **ROOF SEAL MASTIC** using a caulk gun. One tube covers 3 running metres. Apply enough product to all seams and gaps.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

