

# ROOF REPAIR REGULAR

Rubber-based elastic paste for repairs and seals



PRODUCT DATA SHEET



## Product description

Roof Repair Regular is an elastic, rubber-based paste for repairing cracks and blisters the most commonly used building materials.

Roof Repair Regular can also be used for sealing joints, waterproofing roof details and protecting wood.

## Application

For use on all common building materials.

## Advantages

- Environmentally friendly
- Permanently elastic
- Adheres to all materials
- Handy size for small repairs

## Handy tips?

- Store in a cool (max. 25°C) and frost-free place.
- Do not apply if the ambient or substrate temperature is below +5°C.
- Shelf life: at least 12 months in an unopened container. Opened containers have a limited shelf life.

Material	Colour	Contents	Coverage	Drying Time	Coats	Overpaintable
Water-based rubber coating	Black	150 ml	2 L/m <sup>2</sup>	48 hours	At least 2	Yes

# ROOF REPAIR REGULAR

Rubber-based elastic paste for repairs and seals



INSTRUCTIONS



## What do I need?



## How do I prepare the surface?

- First dry and remove all dust and grease from the substrate.

## How do I use the product?

- Apply at least two coats using a brush.
- Dust dry after 3 hours, can withstand water after 12 hours. Fully cured after 48 hours.
- Reinforce larger cracks with **ANTI-CRACK** polyester fleece between 2 layers of **ROOF REPAIR REGULAR**.

## Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or [info@aquaplan.com](mailto:info@aquaplan.com)

The Netherlands: 0162 42 29 00 or [verkoop-dhz@martensgroep.eu](mailto:verkoop-dhz@martensgroep.eu)

Website: [www.aquaplan.com](http://www.aquaplan.com)

