

ROOF COATING GUTTERS

Waterproof renewal coating for gutters made from all commonly used materials



PRODUCT DATA SHEET



Product description

Roof Coating Gutters is a solvent-free, odourless, ready-to-use coating made from flexible hybrid polymers. It is a self-levelling renewal coating for the permanent repair and protection of gutters made from all commonly used materials. When cured it forms a waterproof, maintenance-free, elastic and seamless coating. It protects your gutters from corrosion, acid rain, UV rays and other aggressive environmental influences.

Application

For use on gutters made from all commonly used materials.

Advantages

- › Resistant to all temperatures
- › Highly elastic and covers cracks
- › Adheres to all commonly used materials

How much product do I need?

Roof Coating Gutters is available in a 2.5-litre container. This covers:

- 10 running metres of gutters
- 5 m² surface area

Handy tips?

- Store in a cool (max. 25°C) and frost-free place.
- Do not apply if the ambient or substrate temperature is below +5°C.
- Shelf life: at least 12 months in unopened container. Opened containers have a limited shelf life.
- Stir well before use and close container carefully after use.
- Can withstand rain/water after 12 hours.
Fully cured after 36 hours (depending on ambient conditions).

| Material | Colour | Contents | Coverage | Droogtijd time | Coats | Overpaintable |
|---------------|--------|----------|---------------------|-------------------|-------|---------------|
| MS Polymer | Grey | 2,5 L | 2 m ² /L | 24 hours | 1 | No |

ROOF COATING GUTTERS

Waterproof renewal coating for gutters made from all commonly used materials



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- First dry and remove all dust and grease from the substrate.
- Roughen the surface to be treated with a steel brush and degrease it with a solution of water and ammonia or a synthetic degreaser. Note: only treat new metal after 6 months.
- Cover visible holes with a piece of masking tape to prevent seepage.

How do I use the product?

- Pour **ROOF COATING GUTTERS** onto the prepared substrate and immediately spread it lightly with a brush. Use 0.45 to 0.50 l/m² (coat thickness = ± 0.5 mm). One coat is sufficient. In extreme cases, a second coat can be applied after 24 hours. Reinforce larger cracks with **ANTI-CRACK** polyester fleece between 2 coats of **ROOF COATING GUTTERS**.

Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com



| | | | |
|--------------------------------------------|------------------------------|-------------------------------------|-----------------------------|
| Usage 10 L ± 5 m ² | Drying time 24 hrs | Cleaning H ₂ O | Protection Gloves |
|--------------------------------------------|------------------------------|-------------------------------------|-----------------------------|