

AQUA TAPE

Waterproof, self-adhesive repair tape



PRODUCT DATA SHEET



Product description

Waterproof, self-adhesive tape made from self-adhesive SBS rubber for sealing seams and cracks in drain pipes, roof windows, skylights, etc. and for repairing gutters, roof coverings and leaks on boats, caravans, etc. The front is protected with UV-resistant aluminium foil. This enables **AQUA TAPE** to protect against all weather conditions. **AQUA TAPE** adheres extremely well to almost all substrates thanks to the self-adhesive SBS bitumen layer. It is easy to shape due to its exceptional elasticity. It's also easy to cut and trim.

Application

The applications are almost limitless. Use **AQUA TAPE** for waterproofing seams and cracks in drain pipes, edge trim, roof tiles, window frames, skylights, roof windows, chimneys and gutters made from all kinds of materials, such as lead, zinc, aluminium, stone and concrete. It can also be used to repair roof coverings and leaks on cars, boats or caravans.

Advantages

- › Easily assumes any shape thanks to its elasticity
- › UV resistant
- › Highly adhesive
- › Easy to cut or trim
- › Protects against all weather conditions

How much product do I need?

That depends on the application.

Handy tips?

- Bring **AQUA TAPE** to room temperature ($\pm 20^{\circ}\text{C}$) for 24 hours before application.
- Do not apply if the ambient or substrate temperature is below $+5^{\circ}\text{C}$.
- Available in 2 colours: grey and aluminium.
- Available in the following sizes:

LENGTH	WIDTH
5 m	7,5 cm (grey)
5 m	10 cm (grey and aluminium)
5 m	15 cm (grey)
10 m	10 cm (grey and aluminium)
10 m	15 cm (grey and aluminium)
10 m	22,5 cm (grey)
10 m	30 cm (grey)

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Bitumen and tape	Aluminium Grey	x running metres with a width of x cm	Per running metres	/	1	No

AQUA TAPE

Waterproof, self-adhesive repair tape



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- Dry the surface and remove all dust, rust or other particles.
- First treat porous surfaces with **ROOF PRIMER ROOFING**, which dries quickly (in 3 hours).



How do I use the product?

- Cut or trim the **AQUA TAPE** to length, remove the protective film and apply where necessary. Press firmly so that AQUA TAPE assumes the shape of the substrate. Smooth any creases with a cloth. For long strips, remove the protective film in sections of approx. 40 cm.



Width	Height	Available colours
7,5cm 10cm 15cm 22,5cm	10m 5m	ALUM GREY

Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

