# **ROOF REPAIR WET**

Watertight roof repair paste









#### **Product description**

An elastic repair paste, reinforced with additional fibres, for water-proofing leaks in roofs and gutters under all weather conditions such as rain, fog and frost. Thanks to its exceptional adhesion, ROOF REPAIR WET bonds immediately, even under water, to weathered roofing, metal, masonry, wood, etc. and prevents further water infiltration. Leaks resulting from cracks, open seams, poorly executed detailing on roof edges, skylights, etc. can be plugged during severe weather.

### **Application**

For use on bitumen roofs and gutters. It can also be used on metal, masonry and wood.

#### Advantages

- Adheres to all substrates
- Plugs leaks in rainy weather
- Optimal adhesion even under water
- Reinforced with fibres
- Easy to apply

## How much product do I need?

Depends on the severity of the leakage.

### Handy tips?

- ROOF REPAIR WET is made from uniquely selected bitumen reinforced with fibres.
- Store in a cool, dry place.
- Do not apply if the ambient temperature is below -5°C or above +35°C.
- A leak in your flat roof is often not a one-off event. Additional leaks may occur due to ageing or poorly executed
  detailing in the existing roof covering. We recommend inspecting the roof fully in dry weather and, if necessary,
  repairing it permanently. Prevention is definitely better and cheaper than a cure.
- Clean your tools with white spirit or turpentine.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Special bitumen	Black	1 / 2,5 kg	Depends on the severity of the leakage	About 48 hours	1	Yes

0116

## **ROOF REPAIR WET**

Watertight roof repair paste







#### What do I need?







## How do I prepare the surface?

- First locate the leak. Leaks are usually located around skylights, chimneys, in the vicinity of blisters and/or cracks in the roof covering, around open seams and loose wall flashings.
- Clean the substrate with a stiff brush and wipe up any puddles.



#### How do I use the product?

- Apply ROOF REPAIR WET to the problem area with a putty knife and press firmly.
- Close the container carefully after use. Do not place any weight on it for a few days.







We are ready to answer all your questions. Feel free to contact us:

Belgium: 03 248 30 00 or <a href="mailto:info@aquaplan.com">info@aquaplan.com</a> The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com





