

ROOF COATING EXPERT

Universal and waterproof coating



PRODUCT DATA SHEET



Product description

A universal and elastic coating for the seamless repair and renovation of old and damaged flat roofs and gutters made from any material, even in rainy weather. When dry, it forms a crack-filling, elastic, highly adhesive and waterproof coating. The unique, high-tech composition of **ROOF COATING EXPERT** guarantees immediate waterproofing in a single coat on all dry and damp substrates, even during light rainfall, without requiring a special adhesive layer. The light grey colour also provides UV reflection, resulting in a cooler roof. This extends the life of the roof by at least 7 years.

Application

For use on various substrates such as bitumen roofing membranes, shingles, slates, tiles, wood, corrugated sheets, aluminium, zinc, lead, hard PVC (gutters), concrete, masonry, stone, porous tiles, etc.

Advantages

- Adheres to any substrate
- Waterproofs in any weather
- Repairs and renews with 1 coat
- Ready to use
- High quality, reinforced with synthetic fibres

How much product do I need?

0.9 to 1.8 l/m² depending on the type of substrate and the damage

Handy tips?

- ROOF COATING EXPERT** is made from acrylates and resins and is reinforced with fibres.
- Store in a cool and dry place.
- Do not apply if the ambient temperature is below -5°C or above +35°C.
- Do not apply to bitumen surfaces that are less than 6 months old.
- ROOF COATING EXPERT** is made from acrylates and resins and is reinforced with fibres.
- Clean your tools with white spirit or turpentine.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Acrylic resin	Grey	0,75 L / 4 L / 10 L	0.6 to 1.2 m ² /l	Immediately rainproof and dust dry after about 3 hours, depending on the temperature	1	Yes

ROOF COATING EXPERT

Universal and waterproof coating



INSTRUCTIONS

What do I need?



How do I prepare the surface?

- Ensure that the dry or slightly damp substrate is free of dust and grease. Do not apply to water-saturated substrates or areas that are constantly flooded or covered with ice.

How do I use the product?

- Stir **ROOF COATING EXPERT** well. Apply a single coat thickly and evenly with a brush, roller or floor squeegee at a rate of 0.9 to 1.8 l/m². The amount of product required depends on the type of substrate and the degree of damage. **ROOF COATING EXPERT** is rainproof and dust dry after 3 hours at 20°C.
- In extreme cases, a second coat can be applied after 8 days for additional UV protection.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

