

# RAIN PROTECT LIQUID

Water-resistant interior and exterior wall protection



PRODUCT DATA SHEET



## Product description

Colourless, water-repellent and breathable coating for protecting unpainted interior and exterior walls against rain penetration and dirt. **RAIN PROTECT LIQUID** penetrates deep into any porous substrate and ensures a durable, vapour-permeable moisture barrier against water penetration. This prevents frost damage and combats the formation of moss. **RAIN PROTECT LIQUID** contains no harmful organic solvents and can therefore be used indoors.

## Application

For use on unpainted, vertical, porous interior and exterior walls and façades made of concrete, brick, plaster and sand-lime brick.

## Advantages

- › Colourless and vapour permeable
- › Does not change the appearance of the wall
- › Protects against rain penetration and pollution
- › Environmentally friendly and safe to use
- › Easy to apply

## How much product do I need?

Use approx. 1 litre per 2 m<sup>2</sup> per coat.

See also the calculator on our website [www.aquaplan.com](http://www.aquaplan.com).

## Handy tips?

- Store in a cool (max. 20°C) and frost-free place.
- It cannot be applied to painted or plastered walls.
- Never apply **RAIN PROTECT LIQUID** in direct sunlight or when rain is expected within 4 hours.
- The substrate and ambient temperature must be above +5°C and below +25°C during application and drying.
- Cover adjacent paintwork, sills, windows, glass, window frames, bluestone, tiles, etc. to protect against stains. Remove stains immediately with water.
- **RAIN PROTECT LIQUID** is suitable for virtually all facing bricks. However, more and more pigments are being added to facing bricks. Always carry out a test on an inconspicuous area to check that the appearance of the bricks is not undesirably altered.
- Clean tools with water immediately after use.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Siloxane resin	Transparent	0,75 L / 5 L / 10 L	About 2 m <sup>2</sup> /l per coat	About 1 hr	Min. 2	Yes

# RAIN PROTECT LIQUID

Water-resistant interior and exterior wall protection



INSTRUCTIONS



## What do I need?



## How do I prepare the surface?

- First make sure the surface is free of dust. If the substrate is very dirty, clean it with a pressure washer.
- Remove any paint residue and salt crystals with a stiff brush.
- Treat any green mould, lichens and algae with **GARDEN CLEAN GREEN REMOVER** or **GARDEN CLEAN SCRUB FREE**.
- Seal cracks larger than 0.2 mm with colour-matched mortar or mastic and repair bad grouting.
- Make sure the substrate is reasonably dry before application.



## How do I use the product?

- Shake well before use. **RAIN PROTECT LIQUID** has a milky colour that becomes completely transparent as it dries.
- Apply undiluted **RAIN PROTECT LIQUID** with a brush, roller or garden sprayer from top to bottom until the substrate is saturated.
- Apply to small areas and apply subsequent coats while still wet with a maximum of 1 hour between coats.
- It can be overpainted with acrylic paint systems.



Usage	Drying time	Cleaning	Protection
5L ±10m <sup>2</sup>	1 hrs	H <sub>2</sub> O	Gloves

## Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or [info@aquaplan.com](mailto:info@aquaplan.com)

The Netherlands: 0162 42 29 00 or [verkoop-dhz@martensgroep.eu](mailto:verkoop-dhz@martensgroep.eu)

Website: [www.aquaplan.com](http://www.aquaplan.com)

