ROOF REPAIR TILE-FIX

Waterproof and storm-resistant repair







Product description

Ready-to-use, linseed-based roof repair mortar for anchoring and repairing tiles, ridge caps and lead flashing to make them storm resistant. Adheres immediately, is permanently elastic and waterproof. Due to its unique composition, **ROOF REPAIR TILE-FIX** is extremely easy to apply and can be used for a variety of applications. It can also be used at any temperature.

Application

Used to secure roof tiles, ridge caps and lead flashing. It can also be used to seal draughts and make corrugated sheets, skylights and cable ducts watertight.

Advantages

- Permanently elastic and highly adhesive
- Storm-resistant repair mortar
- Can be used at any temperature
- Overpaintable

How much product do I need?

About 1 to 1.5 m of ridge finish

Handy tips?

- Work gloves are included in the pack.
- Clean your tools with white spirit or turpentine.
- Immediately remove any product residue from the roof tiles with a dry cloth. Clean with white spirit/turpentine (does not apply to glazed tiles).

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
-	Grey	4 x0.25 m and gloves	Approx. 1-1.5 m of ridge finish	None	1	Yes

0116

ROOF REPAIR TILE-FIX

Waterproof and storm-resistant repair







What do I need?







How do I prepare the surface?

- Ensure that the substrate is dry, clean and free of grease.
- Roughen smooth surfaces to improve adhesion.



How do I use the product?

- Wear the supplied gloves.
- Apply a strip of **ROOF REPAIR TILE-FIX** to the top of the highest tiles. Press the ridge cap firmly into the paste. If necessary, remove the gloves so you don't get the ridge dirty.
- Cut away the excess product with a spatula. This can be reused.
- Smooth all joints with a spatula.











We are ready to answer all your questions. Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com







