

ROOF PRIMER ROOFING

Bitumen bonding varnish for roofs



PRODUCT DATA SHEET



Product description

Quick-drying bitumen primer for activating and preparing substrates on which roofing products will be applied. It improves the adhesion when used with bitumen roofing rolls and liquid maintenance and repair products. It adheres well to a variety of substrates and dries exceptionally fast.

Application

For use on many substrates such as old bitumen roofing, concrete, brick, metal, aluminium, lead, etc.

Advantages

- › For all substrates
- › Dries exceptionally fast
- › Ensures optimum adhesion
- › Easy to apply

How much product do I need?

Apply a thin layer and ensure that the metal is completely covered.

Handy tips?

- **ROOF PRIMER ROOFING** is made from bitumen and quick-drying solvents.
- Store in a cool, dry place.
- Do not apply in direct sunlight or if the ambient temperature is below +5°C or above +35°C.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Bitumen and quick-drying solvents	Black	0,5 l	About 5 m ² /l	About 30 min.	1	Yes

ROOF PRIMER ROOFING

Bitumen bonding varnish for roofs



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- Make sure the substrate is dry; remove all dust and grease.



How do I use the product?

- Before use, shake the spray can vigorously until the pea can be heard.
- Apply one thin coat of **ROOF PRIMER ROOFING** to a dry surface.
- Ensure a distance of approx. 30 cm between the nozzle and the surface.
- Allow the primer to dry for 30 minutes before applying any products.
- After use, hold the can upside down and press the nozzle for a few seconds to release some of the primer and prevent clogging.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

