

ROOF PRIMER EPDM

Bonding varnish for EPDM rubber roofs



Product description

Quick-drying bonding varnish to prepare the substrate for the installation of a rubber roof and gutter, an EPDM roof covering. **ROOF PRIMER EPDM** fixes residual dust and loose particles, ensuring optimum adhesion when installing single-ply EPDM in one piece.

Application

For use on old bitumen roofing, wood or concrete before bonding the EPDM membrane with **EPDM GLUE**.

Advantages

- › Dries quickly
- › For all substrates
- › Ensures optimum adhesion
- › Easy to apply

How much product do I need?

- 3 Approx. 4 m²/litre on concrete
- 4 Approx. 5 m²/litre on wood
- 5 Approx. 6 m²/litre on bitumen roofing rolls

Handy tips?

- Store in a cool, dry place.
- Do not apply if the ambient or substrate temperature is below +5°C.
- Clean your tools with white spirit or turpentine.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Primer	Black	4 kg	3 to 6 m ² /l depending on the porosity of the substrate	About 3 hrs	1	Yes

ROOF PRIMER EPDM

Bonding varnish for EPDM rubber roofs



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- Remove all dust and grease from the substrate.



How do I use the product?

- Apply one coat of **ROOF PRIMER EPDM** with a roller or brush, using approx. 0.2 l/m². The consumption is lower for substrates other than bitumen.
- Allow to dry for at least 3 hours.
- Cover with an EPDM membrane in one piece. See the detailed installation instructions for **RUBBER ROOF & GUTTER**.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

