

WALL PROTECT QUICK JOINT

Joint repair mortar



PRODUCT DATA SHEET



Product description

A high-quality, ready-to-use grout for the easy repair of joints between brick and mortar walls or cracks in concrete. It is very easy to apply using a caulking gun. This joint repair compound adheres well to most building materials and is rainproof after only a few hours. It can be sanded and painted.

Application

For use in repairing joints in brick and mortar walls or cracks in concrete. It can be used both indoors and outdoors. It is not suitable for expansion or movement joints.

Advantages

- › Ready-to-use repair agent
- › Quick and easy to use
- › Can be painted over
- › Excellent adhesion to many building materials, including concrete, masonry, stone and cement

How much product do I need?

That depends on the area or details to be treated.

Handy tips?

- **WALL PROTECT QUICK JOINT** is made from a high-quality, hardening acrylic dispersion.
- Store **WALL PROTECT QUICK JOINT** in a cool (max. 25°C), dry and frost-free place.
- Do not apply if the ambient or substrate temperature is below +5°C or above 40°C.
- Do not apply to walls that are in direct sunlight during application.
- Clean your tools with water immediately after use.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Acrylic dispersion	Grey	310 ml	Depends on the area to be treated	About 24 hrs	1	Yes

WALL PROTECT QUICK JOINT

Joint repair mortar



INSTRUCTIONS



What do I need?



How do I prepare the surface?

- Remove all dust and grease from the substrate. Remove any loose bits.

How do I use the product?

- Cut the tube open at the thread, position the nozzle, and then cut it to achieve the desired diameter.
- Apply **WALL PROTECT QUICK JOINT** evenly using a caulking gun, then smooth the product with a wet jointer or putty knife.
- After 5 minutes, remove any excess grout with a hand broom or wet sponge.
- For larger cracks, apply the product in two stages.
- 1 tube is good for about 6 metres of joint repair. Rainproof after 5 hours. It can be painted over after complete curing (24 hours).

Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

